

TREMOL



Cleaning nozzles with **spinning radial jets** (85°/90°). **Nozzle centralizers** are recommended for a better cleaning so the nozzle is lifted from the bottom of the pipe.

To be used for **removal of grease** and **limestone** from pipe walls, pipe cleaning before CCTV inspection or root cutter jobs.

	1/8" F	1/4" F	3/8" F	1/2" F	3/4" F	1" F	1 1/4" F
Width x Length (in)	0.5" x 1.5"	0.9" x 1.8"	***	1.4" x 2.4"	2" x 3.25"	2.75" x 4.1"	2.75" x 4.1"
Weight (lbs)	1 oz	0.22	***	0.66	1.75	5.75	5.75
Jet angle • rotation/break • rear	90°/85° 20°	90°/85° 20°	*** ***	90°/85° 20°	90°/85° 20°	90°/85° 20°	90°/85° 20°
Inserts	drilled	drilled	M4(*)	10 x M4(**)	10 x M6(**)	10 x M6(**)	10 x M6(**)
Flow (GPM)	3 - 6	6 - 8	8 - 12	12 - 25	30 - 50	50 - 80	50 - 120
Pressure (PSI)	2,000 - 4,000	2,000 - 4,000	2,000 - 4,000	2,000 - 4,000	2,000 - 4,000	2,000 - 3,000	2,000 - 3,000
Working DN (in)	0.75" - 2.4"	1.2" - 2.4"	***	2" - 6"	4" - 11.8"	6" - 15.75"	6" - 15.75"
Part numbers	75510.19R	75510.23R	***	75510.14R	75510.35R	75510.250R	75510.27R

(*) M4x5 steel inserts

(**) M6 Hex head inserts

(***) New size, waiting on exact specifications

Centralizer rings

For DN35 nozzles	
DN70	5305.12A
DN100	5305.12B
For DN50 nozzles	
DN125	5350.34A
For DN70 nozzles	
DN150-200	5305.10



Centralizer rings



Tremol 1/2" with DN 100 ring